ethylene (ETFE) copolymers, tetrafluoroethylene-perfluoroalkoxy (PFA) copolymers, poly (vinyl fluoride) (PVF) and poly (vinylidene fluoride) (PVDF) is activated by radiation or chemical initiation in the presence of a monomer, such as styrene, which can be functionalised to contain an ion exchange group.

IN THE CLAIMS:

Please replace claims 3-15, 17 and 18 with the following amended claims.

- 1 3. (Amended) A substrate according to claim 1, wherein the 2 mixed amorphous silica fibres comprise one or more chopped strand(s) of 3 amorphous silica.
- 4. (Amended) A substrate according to claim 1, wherein the amorphous silica fibres comprise a mixture of both microfibres and chopped fibres in the range of from 95:5% to 5:95% by weight of the mixture respectively.
- 5. (Amended) A substrate according to claim 4, wherein the amorphous silica fibres comprise a mixture of both microfibres and chopped fibres in the range of from 70:30% to 30:70% by weight of the mixture respectively.
- 6. (Amended) A substrate according to claim 1, wherein the fibres have a diameter in the range of from 0.1μm to 50μm.
- 7. (Amended) A substrate according to claim 6, wherein the
 fibres have a diameter in the range of 0.4μm to 9μm.
- 8. (Amended) A substrate according to claim 1, wherein the binder comprises a solution or dispersion of ion-exchange polymeric materials, non-ion-conducting polymers, or inorganic materials or mixtures thereof.
- 9. (Amended) A substrate according to claim 1 for use in the preparation of a composite membrane.
- 1 10. (Amended) A composite membrane comprising a porous substrate of fibres and at least one ion-conducting polymer, characterised in that the

3	substrate comprises a porous matrix of mixed amorphous silica fibres bound with a	
4	binder.	
1 2 3	11. which when dried the change in the area.	(Amended) A composite membrane according to claim 10, en boiled in water undergoes less than or equal to about ±9%
1 2	12. wherein the total thic	(Amended) A composite membrane according to claim 10, ckness of the membrane is less that 200μm.
1 2	13. use in a fuel cell.	(Amended) A composite membrane according to claim 10 for
1 2	14. (Amended) A process for the manufacture of a substrate, comprising the steps of	
3 4	(a)	dispersing mixed amorphous silica fibres in water to form a slurry;
5	(b)	depositing the slurry onto a mesh bed to form a network;
6	(c)	drying and compacting the fibre network; and
7	(d)	applying, before or after step (c), a dispersion of binder.
1	15.	(Amended) A process for the manufacture of a membrane,
2	comprising the steps of	
3 4	(i)	forming a porous substrate according to claim 14; and thereafter,
5 6	(ii)	impregnating the porous substrate with a polymeric material to produce a membrane.
1	17.	(Amended) A membrane electrode assembly comprising a
2	composite membrane according to claim 10.	
1 2	18. according to claim 10	(Amended) A fuel cell comprising a composite membrane

Please add the following new claim:

- (Newly Added) A process according to claim 15, wherein 19. 1 mixed amorphous silica fibres are randomly oriented in said porous substrate. 2

Respectfully submitted,

Christopher R. Lewis, Reg. No. 36,201

Attorney for Applicants

CRL/lrb

Dated: April 12, 2001

Suite 301 One Westlakes, Berwyn P.O. Box 980 Valley Forge, PA 19482-0980

(610) 407-0700

The Assistant Commissioner for Patents is hereby authorized to charge payment to Deposit Account No. 18-0350 of any fees associated with this communication.

EXPRESS MAIL Mailing Label No.: EL751749208US Date of Deposit: April 12, 2001

I hereby certify that this paper and fee are being deposited, under 37 C.F.R. § 1.10 and with sufficient postage, using the "Express Mail Post Office to Addressee" service of the United States Postal Service on the date indicated above and that the deposit is addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231.